







Technical Specifications

CONTACT US

CORPORATE OFFICE 136, 25901 114th Avenue Acheson, AB T7X 5A4

CALGARY, AB Suite 1730, 407 2nd Street SW Calgary, AB T2P 2Y3

MIDLAND, TX

Midland, TX 79706

Denver, CO 80202 FREDERICK, CO 4037 Salazar Way

Frederick, CO 80504

US CORPORATE OFFICE

999 18th Street, Suite 2025N

WATFORD CITY, ND 2066 125th Ave NW 4514 South Midkiff Rd. Watford City, ND 58854

> PATENTS: CDN PATENT: 2 699 556 **USA PATENT: 8 584 802**

Canada Toll-Free: 1.844.296.3744 US Toll-Free: 1.855.296.3722



Elevate Safety & Success on-site with WELLEVATOR









Self Contained and Mobile

Ensures flexible site application and efficient work capabilities since external service and power systems are not required.

Light Truck Towable

The platform can be towed to a location with a light truck, saving on costly heavy truck and picker rates.

Increased Crew Safety

The simple setup, integrated safety railings and stable stairs minimize the risk of slips, trips and falls.

Four-Sided Access to Well Head

Our innovative design and adjustable floor panels allow crews to access and work on all sides of the well head.

Hydraulic Control System

The platform's functions are operated via a reliable hydraulic control system with safety features built in.

Trouble-Free Operation

Our platform was designed for a long, trouble-free service life with minimal maintenance to ensure unprecedented uptime.







- Engineered design and certified annually.
- Stable and sturdy work area 2000 lbs load capacity.
- The platform is totally enclosed, with lanyard tie-offs if needed.
- Quick, safe, and easy egress in the event of evacuation.
- Safe and easy to move perfect for single-well or pad projects.
- General setup and tear-out time is less than 30 minutes.
- A one or two member crew (dependant on customer requirements) can transport, setup and operate.
- No picker required for setup or tear-out.
- Eliminates the need for heavy transport equipment, pickers, loaders, or large crews associated with scaffolding setups.



د EFFICIENT